

Administration Manual

To configure the add-on you will find the link in the administration navigation "INTERGATOR Configuration"

Configuration

Use the settings screen to setup the connection between Confluence and your INTERGATOR server.

On the right side of the screen you will already see the INTERGATOR search and can validate that your settings are correct.

Settings

Setting	Description
Proxy Url (required)	URL used for proxy request to your INTERGATOR server.
Public URL	Optional URL to render direct links to INTERGATOR. Proxy URL will be used as fallback.
Facets	You have to configure all search facets users will be able to use. Please contact you INTERGATOR administrator for a list of all facets.
SSL	Check, if your INTERGATOR server is using any kind of invalid SSL certificate.
Anonymous access	Check to allow searches for anonymous users
Link to INTERGATOR	Check to show INTERGATOR links for anonymous users as well.
Anonymous user	Searches from anonymous users will be done on behalf of this user.
Authentication	• PREAMUTH (recommended): User • Basic Auth (for testing purposes and not recommended for production): You can define a fixed basic auth user. This is only recommended for testing purposes and not for final production usage. All search requests will be done on behalf of this user.
PREAMUTH Header	HTTP header which is used for PREAMUTH authentication and used to send the username.
Basic Auth Username	Username for Basic Auth authentication
Basic Auth Password	Password for Basic Auth Authentication
Cache	Activate local caching for thumbnails of search results
Cache Expiration	Determine how long (in milliseconds) thumbnails are cached in local home directory. Default of 86400000 milliseconds corresponds to 24 hours.
Replace Quick Search	Activate to open INTERGATOR embedded search instead of quick search.
Placeholder	Specify the placeholder that appears in the search field. Default is "*"

Extended Search Parameters

Configure the extended search parameters for request to the INTERGATOR.

Parameter	Description
Lenient	Check if requests should be lenient.
Synonyms	Check if synonyms should be considered.

Stemming	Check if stemming should be enabled.
Correct Query	Check if search queries can be corrected by INTERGATOR API.
Log search	Check if search should be logged in INTERGATOR.

PREAUTH authentication on INTERGATOR Server

We highly recommend using **PREAUTH** as authentication method for intergator in production usage. This is the only method, the search is done on behalf of the authenticated Confluence user.

To be able to use PREAUTH your INTERGATOR server has to be configured supporting PREAUTH.

For more information on this, consider following documentation: [Configure PREAUTH authentication](#)

Please contact your interface projects if you need support for configuring PREAUTH.

[Go to INTERGATOR support](#)

Embedded Search

The embedded search dialog similar to the Confluence quick search. If activated of in addon configuration search field in header instead of the quick search of Confluence will be shown.

Custom usage of embedded search

To open embedded search in your theme or environment you can dispatch the "moewe.addons.intergator:embedded-search" event with default query to open embedded search from everywhere.

```

window.dispatchEvent(new CustomEvent("moewe.addons.intergator:embedded-search", {
  detail: {
    query: "*" // or default query when embedded search opens
  }
}));

```

To add custom javascript you will find here more information under this [link \(How to use JavaScript in Confluence\)](#).